

Prelude Square



Prelude Square Black 1500lm 3000K Ra>90 Trailing edge dimming

Article code: 111390
EAN: 7021981113902



Electrical

System wattage: 16W
Voltage: 220-240V
Frequency (Hz): 50/60Hz

Light technic

Type of light source: LED
Luminous flux: 1500lm
Efficacy: 94 lm/W
Colour temperature: 3000K
Colour rendering (CRI): Ra>90
MacAdams factor: SDCM: 3
Lifetime: L90/B10>50,000
Lifetime: L80/B10>60,000
Light distribution: Direct
Optic: Acrylic diffuser

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class II

Energy and approvals

Contains light source of energy class: E
Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
Colour: Black (RAL 9004)
Optics: Acrylic (PMMA)

Mounting/Connection



Mounting: Surface, Indoor
Connection: Screwless terminal block

Dimensions

Width (mm) W: 519
Height (mm) H: 59
Depth (D): 62
Weight (kg) gross/net: 0.898 / 0.799

Packaging

Packing dimensions (mm): 528 x 65 x 65



7 0 2 1 9 8 1 1 1 3 9 0 2