

Canto 2000 Graphite 1400lm 3000K Ra>80 Trailing edge dimming

Article code: 643866
 EAN: 7021986438666

**Electrical**

System wattage: 14W
 Voltage: 220-240V
 Max. luminaires per circuit breaker: B10: 19, B16: 30, C10: 31, C16: 51

Light technic

Type of light source: LED
 Luminous flux: 1400lm
 Efficacy: 100 lm/W
 Colour temperature: 3000K
 Colour rendering (CRI): Ra>80
 MacAdams factor: SDCM: 3
 Lifetime: L70/B50>100,000
 Light distribution: Direct
 Optic: Opal
 Beam angle: 110°
 Photobiological safety: RG 0

Control/Dimming

Type: Trailing edge dimming

Protection

Luminaire class: Class I
 Fire protection class: 850°C - 30s

Energy and approvals

Contains light source of energy class: E
 Breeam: Fulfils Hea 01 for flicker free lighting

Materials and finish

Housing: Aluminium
 Colour: Graphite
 Optics: UV-stabilized polycarbonate

Mounting/Connection

Mounting: Surface, Indoor / Outdoor
 Module: 2000
 Connection: Screwless terminal block

Dimensions

Height (mm) H: 120
 Diameter (mm) D: 325
 Weight (kg) gross/net: 2.35 / 1.94

Packaging

Packing dimensions (mm): 340 x 340 x 120

