

ToLEDo Retro Ball Dimmable ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL 0029493



Product features

- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps
- The versatile ToLEDo Retro ball range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications
- Same look, size and functionality as incandescent lamps
- Omni-directional light distribution
- Gives same sparkling light effect as the incandescent lamp
- Dimensionally identical to incandescent lamps fits all fixtures
- Environment-friendly no mercury and lower CO2 emissions
- Dimmable with approved dimmers



NOTES

undefined

PRODUCT OVERVIEW

Product name	ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740942
Warranty	3 years
Useful luminous flux (Fuse)	470
Luminous flux (Im)	470
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Power consumption (W)	4.5
Wattage (W)	4.5
Dimmable	Yes
Average life (Nominal) (h)	15000
Product EAN number	5410288294933



ToLEDo Retro Ball Dimmable ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL

0029493

DATA TABLE

/\	
General data	
Product name	ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL
Technology	LED
Watt (Rated) (W)	4.5
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-10°C+45°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740942
Warranty	3 years
Optical data	
Useful luminous flux (Fuse)	470
Luminous flux (lm)	470
Luminous flux (Rated) (Im)	470
Correlated colour temperature (k)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70
Electrical data	
Power consumption (W)	4.5
Wattage (W)	4.5
Equivalent watt (W)	40
Primary Supply/Product voltage - min (V)	220
Primary Supply/Product voltage - max	240
(V)	
Control gear required	No
No. Of switching cycles before premature failures	>50000
Dimmable	Yes
Inrush Current (A)	1.2
Inrush Duration (µs)	520
Lamp Energy Label (class)	F
Max. products per 16A C Breaker	133
Max. products per 16A B Breaker	66
Lifetime data	
Lifespan L70 B50	15000
Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000
, , ,	



ToLEDo Retro Ball Dimmable ToLEDo RT Ball V5 ST DIM 470LM 827 E27 SL 0029493

/sica	

Nominal Product Length (mm)	78
Nominal Product Diameter (mm)	45
Weight (kg)	0.045


Packaging

0 0	
Product EAN number	5410288294933
Packaging single length / height (cm)	9.5
Packaging single width (cm)	5.0
Packaging single depth (cm)	5.0
DUN14 (outer)	15410288294930
Units per outer package	6
Packaging outer length / height (cm)	15.8
Packaging outer width (cm)	10.7
Packaging outer depth (cm)	10.5

Safety data

Optimal operating condition (°C)	-10-45
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY



TECHNICAL DRAWINGS

