


START eco Flood Flat PIR
START eco Flood Flat IP54 PIR 2800lm 840
0047967



Product features

- The new Start eco Flood Flat comes with improved design. The streamlined, durable, lightweight die-cast aluminium body makes it a perfect choice for building facades, car parks, garages and construction areas. The product includes 1 m pre-wired stripped cable and fitting bracket for quick and easy installation and the universal mounting bracket allows wall or surface mounting with the possibility of vertical tilting. Black die-cast aluminum housing, white reflector, 2850 lm, 31 W, 92 lm/W, 4000K, drive current 116 mA, non dimmable, CRI>80, IP54, IK06 - fixture, IK05 - sensor, Class I, lumen maintenance L70:B50: 30000 hrs, 156 x 178 x 67 mm (L x W x H). Weight: 0.61kg. PIR sensor included. Energy class: A++ A+ A.




PRODUCT OVERVIEW

Product name	START eco Flood Flat IP54 PIR 2800lm 840
Technology	LED
Housing	Aluminium
General application	Residential & Consumer
ETIM Class	EC001744
E-number FI	4579436
Warranty	3 years
Useful luminous flux (Fuse)	2850
Fixture luminous flux (lm)	2850
Luminaire efficacy (lm/W)	92
Correlated colour temperature (k)	4000
Light colour	Neutral White
CRI (Ra)	80
Beam Angle (°)	110
Photobiological Risk Group	RG1
Total power consumption (W)	31
Electrical protection	Class I
Housing colour	RAL 9017 - Traffic black
IP rating	IP54
IK rating	IK05
Product EAN number	5410288479675

PHOTOMETRY

START eco Flood Flat PIR
START eco Flood Flat IP54 PIR 2800lm 840
0047967



TECHNICAL DRAWINGS

