

**SCHUKO socket outlet 16 A 250 V~ with increased contact protection (Safety Plus)  
Plug terminals**



| Specification                                                                                         | Order No. | Packing unit | PS | EAN           |
|-------------------------------------------------------------------------------------------------------|-----------|--------------|----|---------------|
|  cream white glossy | 4453 01   | 10/100       | 01 | 4010337093718 |
|  pure white glossy | 4453 03   | 10/100       | 01 | 4010337093732 |
|  pure white matt   | 4453 27   | 10/100       | 01 | 4010337093763 |
|  anthracite        | 4453 28   | 10/100       | 11 | 4010337093770 |
|  colour aluminium  | 4453 26   | 10           | 11 | 4010337093756 |
|  black matt        | 4453 005  | 10/100       | 11 | 4010337093701 |
|  grey matt         | 4453 015  | 1/5          | 11 | 4010337093725 |
|  stainless steel   | 4453 600  | 1/5          | 11 | 4010337093787 |

## Features

- The support ring is earthed in connection with the mounting claws and claw screws.
- Quick mounting (approx. 3.5 turns per mounting claw).
- Expanding claws in the housing.
- Easier claw mounting thanks to robust PZ1 / slotted / PH screw head drive.
- Simplified installation thanks to patented arrangement of the large keyhole profiles using box screws.
- Low installation depth.
- Large, ergonomically shaped release levers.
- Sturdy earth bar with solid earthing fingers.
- Sturdy and corrosion-resistant steel support ring.
- Shatter-proof thermoplastic base.

---

## Technical data

|                                 |                                            |
|---------------------------------|--------------------------------------------|
| Installation depth:             | 32 mm                                      |
| Conductors:                     | Rigid and flexible                         |
| Connection cross section        |                                            |
| - for conductors from:          | 1.5 mm <sup>2</sup> to 2.5 mm <sup>2</sup> |
| Ambient temperature             |                                            |
| - increased contact protection: | 0°C to +45°C                               |

---

## Notes

- Increased contact protection (Safety Plus) in accordance with IEC 60884-1.
-