

# Socket outlet 2-way master QC black 9017

Reference STA501002



|                |                      |
|----------------|----------------------|
| Activity       | Installation systems |
| Product family | Wiring Devices       |
| Brand          | Stago                |
| Range          | WGX-W                |

## Base

|                |                      |
|----------------|----------------------|
| Activity       | Installation systems |
| Product family | Wiring Devices       |
| Brand          | Stago                |
| Range          | WGX-W                |
| GTIN           | 7321679003035        |

## Commercial and Web

|                              |                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------|
| Short description            | Socket outlet 2-way master QC black 9017                                                                |
| Medium description           | Socket outlet 2-way master quick connect F80 - with label window - plastic halogen free - black RAL9017 |
| Length                       | 116 mm                                                                                                  |
| Width                        | 84 mm                                                                                                   |
| Height                       | 52 mm                                                                                                   |
| Material                     | Plastic                                                                                                 |
| Colour                       | Black RAL9017                                                                                           |
| Wiring Device Component Type | W815Q                                                                                                   |

## ETIM (EC000125-Socket outlet)

|                                          |                             |
|------------------------------------------|-----------------------------|
| Model (EF000010)                         | Protective contact (type F) |
| Protective contact (EF001033)            | *                           |
| Protective earth pin round (EF012000)    | *                           |
| Number of active pins (round) (EF011998) | 4                           |

|                                                   |                            |
|---------------------------------------------------|----------------------------|
| Number of active pins (flat) (EF011999)           | 0                          |
| With signal lamp (EF000198)                       | No                         |
| With built (EF009258)                             | No                         |
| Type of USB power supply (EF015873)               | *                          |
| Number of units (EF000074)                        | *                          |
| Number of modules (module system) (EF009573)      | *                          |
| Number of socket outlets switchable (EF008814)    | 0                          |
| Number of phases (EF000351)                       | 1                          |
| Imprint/indication (EF003823)                     | None                       |
| Connection type (EF000124)                        | Push-in clamp              |
| With hinged lid (EF000117)                        | No                         |
| With enhanced contact protection (EF000389)       | Yes                        |
| Label space/information surface (EF001035)        | Yes                        |
| Colour (EF000007)                                 | Black                      |
| RAL (EF003882)                                    | 9017                       |
| Metallic colour (EF015260)                        | No                         |
| Transparent (EF006243)                            | No                         |
| Lockable (EF000113)                               | No                         |
| Eject (EF001051)                                  | No                         |
| Insulated mounting (EF001588)                     | Yes                        |
| With function lighting (EF008861)                 | No                         |
| With orientation lighting (EF008862)              | No                         |
| Over voltage protection (EF001332)                | No                         |
| Fault current protection (EF001333)               | No                         |
| With miniature fuse (EF006571)                    | No                         |
| Special power supply (EF001334)                   | No special power supply    |
| Mounting method (EF000003)                        | Wall duct                  |
| Type of fastening (EF002442)                      | Snap mounting (engagement) |
| Material (EF002169)                               | Plastic                    |
| Material quality (EF001257)                       | Thermoplastic              |
| Halogen free (EF000025)                           | Yes                        |
| Surface protection (EF000139)                     | Lacquered                  |
| Surface finishing (EF006569)                      | Matt                       |
| Anti (EF023790)                                   | No                         |
| With on/off switch (EF000488)                     | No                         |
| With loop through function (EF006604)             | No                         |
| Rotated central insert (EF001331)                 | Yes                        |
| Nominal current (EF000001)                        | 16 A                       |
| Nominal voltage (EF000002)                        | 250 V                      |
| Frequency (EF000416)                              | 50 Hz                      |
| Rated fault current (EF002358)                    | * mA                       |
| Suitable for degree of protection (IP) (EF006755) | IP20                       |
| Impact strength (EF004293)                        | *                          |
| Device width (EF008808)                           | 84 mm                      |
| Device height (EF008809)                          | 52 mm                      |

|                                                    |        |
|----------------------------------------------------|--------|
| Device depth (EF008810)                            | 116 mm |
| Compatible with Apple HomeKit (EF014925)           | No     |
| Compatible with Google Assistant (EF014926)        | No     |
| Min. depth of built (EF012278)                     | 52 mm  |
| Compatible with Amazon Alexa (EF014927)            | No     |
| IFTTT support available (EF011072)                 | No     |
| For heavy conditions (according to VDE) (EFDE0005) | No     |

## Logistic

|                   |          |
|-------------------|----------|
| Pack 1 type       | Bag      |
| Quantity pack 1   | 1        |
| Weight pack 1     | 0.17 kg  |
| Length pack 1     | 116 mm   |
| Width pack 1      | 84 mm    |
| Height pack 1     | 52 mm    |
| Pack 2 type       | Carton   |
| Quantity pack 2   | 10       |
| Weight pack 2     | 2.07 kg  |
| Length pack 2     | 330 mm   |
| Width pack 2      | 240 mm   |
| Height pack 2     | 90 mm    |
| Pack 3 type       | Carton   |
| Quantity pack 3   | 40       |
| Weight pack 3     | 8.3 kg   |
| Length pack 3     | 395 mm   |
| Width pack 3      | 260 mm   |
| Height pack 3     | 350 mm   |
| Pack 4 type       | Pallet   |
| Quantity pack 4   | 720      |
| Weight pack 4     | 155 kg   |
| Length pack 4     | 1200 mm  |
| Width pack 4      | 800 mm   |
| Height pack 4     | 870 mm   |
| Customs code      | 85366990 |
| Net weight        | 0.17 kg  |
| Country of origin | CN       |

## Certification

|            |          |
|------------|----------|
| ETIM class | EC000125 |
|------------|----------|

## Status product

For the latest information check [http://wieland-group.com/cable-support-systems/installation-systems/wiring-devices/socket-outlets\\_wd/socket-outlet-2-way-master-qc-black](http://wieland-group.com/cable-support-systems/installation-systems/wiring-devices/socket-outlets_wd/socket-outlet-2-way-master-qc-black)