

LED waterproof light fitting

MODUS PL5000, wide body 1275mm, LED 840 , body PE, opal PC cover, IP65, driver 1400mA, emergency pack 3h

Code: PL5000M2W4ND/NZ3

EAN: 8596099001018



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP65
Color housing:	Grey	Impact strength:	IK08
Suitable for suspended mounting:	Yes	Material housing:	Plastic
Suitable for surface mounting:	Yes	Rated ambient temperature (°C):	-10...+45
Suitable for ceiling mounting:	Yes		

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	5500
System power (W):	40	Luminaire efficacy (lm/W):	138
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	CO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Rozměry

Length (mm):	1275	Width (mm):	135
Height/depth (mm):	100	Built-in length (mm):	800
Size version:	M	Weight (kg):	3

Elektrické vlastnosti

Protection class:	I	Voltage type:	AC
Autonomy (h):	3	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Suitable for emergency lighting:	Yes	No dim function:	Yes