

UNIVERSAL CLIP - IT FITS!

NEW!

NEW!

Our new universal clip lets you fix your installation as easy as never before.

Universal:

- for rigid and flexible pipes in all diameters
- halogenfree
- fast-click-on
- adjustable - move it left and right to align your installation



IPM-E-LF

LIGHT > 320 N / 5 cm

In 3 m lengths with or without moulded on couplers (installation conduit) as per IEC 614-2-2, EN 50086-2-1

Designation: EN 22211, IEC 205

Material: PVC-U

Colour: grey, RAL 7035

Temperature range: - 5° to + 60° C

Material Characteristics: PVC-U is flame resistant, resistant to acids and bases

Application: Developed as an installation aid for open surface installation as well as for installation under plaster. IPM-E-LF guarantees a clean and professional installation.



IPM-E-LF Type	16	20	25	32	40	50	63
Art.-Nr.	21315016	21315020	21315025	21315032	21315040	21315050	21315063
Outside Ø mm	16	20	25	32	40	50	63
Inside Ø mm	14,3	18,3	22,6	29,4	37,0	46,4	59,2
Bundle contents m	111	111	57	57	21	21	21
Master bundle m	3885	2775	1710	1140	630	378	252

Universal Coupler	16	20	25	32	40	50	63
Art.-Nr.	21380016	21380020	21380025	21380032	21380040	21380050	21380063
Pieces per box	50	100	100	50	25	10	5

Bend	16	20	25	32	40	50	63
Art.-Nr.	21385016	21385020	21385025	21385032	21385040	21385050	21385063
Pieces per box	50	50	50	50	25	10	5

Universal Clip	16	20	25	32	40	50	63
Art.-Nr.	21310116	21310120	21310125	21310132	21310140	21310150	21310163
Pieces per box	100	100	100	100	50	25	25

