




# ROUNDLINE

## Roundline Reco

### The best comfort and economy

This heater is chosen for your regular household or if you would like to control your heaters wireless. The electronic thermostat gives a temperature stability of  $\pm 0,1^{\circ}\text{C}$  regardless of the outdoor temperature. When additional heat emerges in the room the heater shuts off completely before the temperature rises even  $\pm 0,5^{\circ}\text{C}$  in the room. Roundline Reco has a flat front. The end of the heater has a sinkage where the thermostat control, the power switch and the light emitting diode are placed. In the sinkage the radio receiver for wireless control is placed (sold separately).



### ACCESSORIES

**Wireless control** - Gives you many ways to save more energy  
Roundline Reco can be complemented with a small receiver (placed in the end of the heater) that communicates with a small room unit. Several radio receivers can be connected to the same spot. The room unit gets an extra thermostat. The wireless control unit is as suitable for houses with open construction plan as in rooms where extra comfort is needed, like a bedroom. With a press of a button, the temperature is lowered during the night. After six hours it automatically returns to standard setting. An airing function prevents the heater from rushing when you open a window or door for airing.

### ROUNDLINE IS A SAFE RADIATOR

Roundline will never be hotter than  $70^{\circ}\text{C}$  on the surface. In normal running (50% load 230V/400V) it means that the temperature of the surface is approx.  $35^{\circ}\text{C}$ .

**Overheating protection device:** The heater is equipped with an overheating protection device, which turns the heater off if the heater of some reason would become too hot. Do not cover the heater!

**No sharp corners:** Roundline has no hard corners and no sharp edges to be aware of.

Roundline can be turned forward or removed from its bracket when there is a need tidying up or when restoring.

### SERVICE

With further questions, please contact:

Tego Customer Service Phone +46 418 45 58 25

Wattage	Length	Height	Volt	Order no	Order no
Standard temperature P21			Perm. install.	Cable & Plug	
400	638	200	230	E 8511604	E 8511664
			400	E 8511605	
600	750	200	230	E 8511606	E 8511666
			400	E 8511607	
800	974	200	230	E 8511608	E 8511668
			400	E 8511609	
1000	1198	200	230	E 8511610	E 8511670
			400	E 8511611	
1200	1422	200	230	E 8511612	E 8511672
			400	E 8511613	
300	414	400	230	E 8511624	E 8511674
			400	E 8511625	
600	638	400	230	E 8511626	E 8511676
			400	E 8511627	
800	750	400	230	E 8511628	E 8511678
			400	E 8511629	
1000	974	400	230	E 8511630	E 8511680
			400	E 8511631	
1200	1198	400	230	E 8511632	E 8511682
			400	E 8511633	
1500	1422	400	230	E 8511634	E 8511684
			400	E 8511635	
Extra low temperature IP21					
450	750	400	230	E 8511654	
			400	E 8511655	
600	1198	400	230	E 8511656	
			400	E 8511657	
750	1500	400	230	E 8511658	
			400	E 8511659	
Accessories					
Radio receiver			E 8511690		
Room unit			E 8511691		



TEGO SYSTEM AB, Box 43, SE-261 22 Landskrona, Tel +46 (0)418-45 58 00, Fax +46 (0)418-45 58 01  
Bg 5625-3735, Pg 3 58 97-8, Nordea SWIFT NDEASESS IBAN SE47 3000 0000 0307 6181 0730  
Vat no SE556124910201, Styrelsens säte: Landskrona, Innehar F-skattsedel, [www.tego.se](http://www.tego.se), [info@tego.se](mailto:info@tego.se)