



- Available in a wide range of material and sizes
- Made from 100% high quality plastic, allows for good recycling
- Inside serration for a strong hold onto bundles
- Easy application either manually or with a processing tool
- Simply to insert due to bent tail

RoHS ✓



[All catalogue pages](#)



Application Tool	MK6, MK6PN, MK9, MK9HT, MK21
Colour	Blue (BU)
Fixation Method (FF)	None
Identification Plate Position	none
Manufacturer Short Description calculated	T120R E/TFE BU 50
Product Family	T-Series in E/TFE
Product Group	Cable Ties for higher chemical resistance for temperatures up to +170°C in Ethylentetrafluorineethylene
Releasable Closure (Yes/No)	No
Tie Closure	plastic pawl
Type	T120R-TZ
Variant	Inside Serrated

Bundle Ø max.	105.0 mm
Bundle Ø max. (imperial)	4.1 "
Bundle Ø min.	15.0 mm
Bundle Ø min. (imperial)	0.59 "
Cable Tie Head Height (Metric)	8.7 mm
Cable Tie Head Length (metric)	12 mm
Cable Tie Head Width (metric)	12.95 mm
Length (L)	387.0 mm
Length (L) (imperial)	15.2 "
Min. Tensile Strength (lbs)	120.0 lbs
Min.Tensile Strength (N)	535.0 N
Strap Width max. (G) (imperial)	0.51 "
Strap Width max. (G) (imperial)	0.47 "
Thickness (T)	1.9 mm
Thickness (T) (imperial)	0.075 "
Width (W)	7.4 mm
Width (W) (imperial)	0.29 "

Carton Quantity	2000 pcs.
EAN / GTIN	4031026316833
Pack Cont.	50
Weight	5.2 kg

<http://www.hellermannntyton.com/site/products/cable-ties-inside-serrated/t120r/111-01125>

ELV compliant Dir. Art. 4 (2)	YES
Flammability	UL94 V0
Material	E/TFE
Material	Ethylene Tetrafluoroethylene (E/TFE)
Operating Temperature	-80 °C to +170 °C
REACH compliant Regu. Art. 33	YES
UL OCD link	Link
UL-File Number	E193818

More Information

UNSPSC Key	39121703
------------	----------