

- Schuko power socket 33°
  - Rastec 45 2-pole 16 A / 250 V
  - Spring-loaded terminals
  - Dimensions of single module: 45 x 45 mm
  - Dimensions of double module: 45 x 90 mm
  - Dimensions of triple module: 45 x 135 mm
- Available colours**
- RAL 9010, pure white
  - RAL 2004, pure orange
  - RAL 6029, mint green



ESR1339010

#### Schuko power socket 33° Rastec 45, single

| Designation                              | PU | Order no.         |
|------------------------------------------|----|-------------------|
| Schuko power socket single Rastec 33G rw | 20 | <b>ESR1339010</b> |
| Schuko power socket single Rastec 33G ro | 20 | <b>ESR1332004</b> |
| Schuko power socket single Rastec 33G mg | 20 | <b>ESR1336029</b> |



ESR2339010

#### Schuko power socket 33° Rastec 45, double


| Designation                              | PU | Order no.         |
|------------------------------------------|----|-------------------|
| Schuko power socket double Rastec 33G rw | 1  | <b>ESR2339010</b> |
| Schuko power socket double Rastec 20G ro | 1  | <b>ESR2332004</b> |
| Schuko power socket double Rastec 33G mg | 1  | <b>ESR2336029</b> |



ESR3339010

#### Schuko power socket 33° Rastec 45, triple

| Designation                              | PU | Order no.         |
|------------------------------------------|----|-------------------|
| Schuko power socket triple Rastec 33G rw | 1  | <b>ESR3339010</b> |
| Schuko power socket triple Rastec 33G ro | 1  | <b>ESR3332004</b> |
| Schuko power socket triple Rastec 33G mg | 1  | <b>ESR3336029</b> |



EUS315

#### Overvoltage fine protection

##### Properties:

- The overvoltage protection conductor is designed for line-side fine protection of electronic equipment and is provided, in particular, for installation in device casings, with acoustic fault signalling.
- EUS315 - Overvoltage protection module with 3 connecting lines, each 1.5 mm<sup>2</sup>, for connection of a single or multiple socket
- EUS615 - Overvoltage protection module with 6 connecting lines, each 1.5 mm<sup>2</sup>, for through wiring of several single sockets or multiple sockets

| Designation                                                  | PU | Order no.     |
|--------------------------------------------------------------|----|---------------|
| Fine protection with 3 connections, each 1.5 mm <sup>2</sup> | 1  | <b>EUS315</b> |
| Fine protection with 6 connections, each 1.5 mm <sup>2</sup> | 1  | <b>EUS615</b> |