



SEARCH

Product features TRS - RUTASEAL® TRS - RUTASEAL® EPDM Metric RAL7001


RUTASEAL® - Animation

Product data TRS - RUTASEAL®
Metric

Product data TRS - RUTASEAL® PG

Product data TRS - RUTASEAL
LIGHT®

Installation TRS - RUTASEAL®



Material

Protection class

Temperature range

Test standard

Semko report

Tariff No.

UNSPSC Code

Halogen-Free

EPDM

IP67 acc. to EN 60529

-40°C...+110°C (1)

EN60670-1:2005, EN60529:

1991+A1

1301727, 1026167 (M63),

1122298 (M12F, M16F)

4016930090

39121431

(1) Unstressed material.

Grey RAL 7001

E-number	Size	For cable Ø mm	A mm	B mm	D mm	H mm	H1 mm	Pcs/pack
1458233	M12	4 - 7	12.5	0,5-2	20	12,7	5.4	50
1458234	M16	5 - 9	16.5	1-4	21	18	10.5	50
1458235	M20	8 - 13	20.5	1-4	25,5	20	12.7	50
1458236	M25	11 - 17	25.5	1-4	30,5	21,6	14.5	50
1458237	M32	15 - 20	32.5	1-4	38,5	24,8	17.5	25
1458238	M40	19 - 28	40.5	1-4	48,5	30	20.4	25
1458239	M50	27 - 35	50.5	1-4	60,5	35	23.9	10
1458240	M63	34 - 45	63.5	1-4	73,5	40	28.9	5

Tapper Sealing Technology AB
Lerbacksgatan 2
SE-571 38 Nässjö
Sweden

Telephone: +46 380 558180
Fax: +46 380 12303

